

Verti-Cut Flex 2000

Efficient thatch removal on contoured and undulating turf. Multiple points of flexibility and floating wings follow changes in elevation. Passive Pivoting Suspension™ allows pivoting around curves, bends, trees and obstacles. Heavy-duty dampers stabilize the machine while in work.



Specifications

SKU	S0001602
Operation	PTO drive
Working width (m)	2.0
Working width (inch)	79
Max. Working depth (mm)	40
Max. Working depth (inch)	1.6
Max. Working speed (km h)	5
Max. Working speed (mph)	3.1
Weight (kg)	420
Weight (lbs)	926
Standard knife thickness (mm)	2
Standard knife thickness (inch)	5.6
Distance between knives (mm)	25 - 50
Distance between knives (inch)	1 - 2
Min. Tractor HP required	30
Min. Lifting capacity 610 mm behind the lifting eyes (kg)	520
Min. Lifting capacity 24 inch behind the lifting eyes (lbs)	1146
Max. capacity (m² hr)	10000
Max. capacity (ft² hr)	107639
Three-point hitch	Cat. 1
Rpm Max.	540

Distributed by:



www.centaur-asiapacific.com
info@centaur-asiapacific.com

*Hong Kong, Macau, Malaysia (Johor).